

FORM PTO-1390
(REV 10-97)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

DATE: October 22, 1999

EXPRESS MAIL LABEL NO.
EM341130405USATTORNEY DOCKET NO.
36256/DBP

U.S. APPLICATION NO.

To Be Assigned
09/403472TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371INTERNATIONAL APPLICATION NO.
PCT/IL98/00204INTERNATIONAL FILING DATE
29.April.1998PRIORITY DATE CLAIMED
01.May.1997

TITLE OF INVENTION

OPTICAL RESONATORS WITH DISCONTINUOUS PHASE ELEMENTS

APPLICANT(S) FOR DO/EO/US


Yochay Danziger; Asher Friesem; and Ram Oron

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2)).
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/LUS).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)).
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). (UNEXECUTED)
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items below concern other document(s) or other information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Small entity claim with a copy of this transmittal letter attached.
17. ☒ International search report.
18. ☒ International preliminary examination report.
19. ☒ Extra set of drawings
20. ☐
21. ☐

U.S. APPLICATION NO. (If known, see 37 CFR 1.51) To Be Assigned 09/403472		INTERNATIONAL APPLICATION NO. PCT/IL98/00204		ATTORNEY DOCKET NO. 36256/DBP			
<input checked="" type="checkbox"/> The following fees are submitted: (see Note (1) below) Basic National Fee (37 CFR 1.492(a)(1)-(5)): Search Report has been prepared by the EPO or JPO \$ 840.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) ... \$ 670.00 No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) \$ 760.00 Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$ 970.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) \$ 96.00 ENTER APPROPRIATE BASIC FEE AMOUNT = \$ 840.00				CALCULATIONS		PTO USE ONLY	
Surcharge of \$130 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$ 130.00			
Claims	Number Filed	Number Extra	Rate				
Total Claims	15+2 -20=	0	X \$18	\$ 0.00			
Independent Claims	1 -3=	0	X \$78	\$ 0.00			
Multiple dependent claim(s) (if applicable)			+ \$260	\$ 260.00			
TOTAL OF ABOVE CALCULATIONS =				\$ 1,230.00			
Reduction by 1/2 for filing by small entity, if applicable. Verified Small entity statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).				\$			
SUBTOTAL =				\$ 1,230.00			
Processing fee of \$130 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$			
TOTAL NATIONAL FEE =				\$ 1,230.00			
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$			
TOTAL FEES ENCLOSED =				\$ 1,230.00			
Note (1): The basic national fee must be paid when filing this application. The 20-month time limit (37 CFR § 1.494) and 30-month time limit (37 CFR § 1.495) are not extendable.				Amount to be: refunded \$			
				charged \$			
a. <input checked="" type="checkbox"/> A check in the amount of \$ 1,230.00 to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 03-1728 . A duplicate copy of this sheet is enclosed.							
NOTE (2): Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.							
SEND ALL CORRESPONDENCE TO:							
D. Bruce Prout CHRISTIE, PARKER & HALE P.O. Box 7068 Pasadena, CA 91109-7068				By  D. Bruce Prout Reg. No. 20,958			

Docket No. : 36256/DBP/C608 CHRISTIE, PARKER & HALE, LLP
 Applicant or Patentee : Yochay Danziger et al. Post Office Box 7068
 Application or Patent No. : To Be Assigned Pasadena, CA 91109-7068
 Filed or Issued : To Be Assigned (626) 795-9900
 Entitled : OPTICAL RESONATORS WITH DISCONTINUOUS PHASE
 ELEMENTS

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS
 (37) CFR 1.9(f) & 1.27(c) – SMALL BUSINESS CONCERN**

I hereby declare that I am

 the owner of the small business concern identified below:

 X an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF SMALL BUSINESS CONCERN : Yeda Research and Development Co. Ltd.

ADDRESS OF SMALL BUSINESS CONCERN : P.O. Box 95, 76100 Rehovot, Israel

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.12, and reproduced in 37 CFR 1.9(d), for the purposes of paying reduced fees to the United States Patent and Trademark Office, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention entitled **OPTICAL RESONATORS WITH DISCONTINUOUS PHASE ELEMENTS** by inventor(s) described in

 X the specification filed herewith

 Application No. filed

 Patent No. issued

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights in the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e). *NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

NAME :
 ADDRESS :

 INDIVIDUAL SMALL BUSINESS CONCERN NONPROFIT ORGANIZATION

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS
(37) CFR 1.9(f) & 1.27(c) - SMALL BUSINESS CONCERN

Docket No.: 36256/DBP/C608

NAME :

ADDRESS :

☐ INDIVIDUAL

☐ SMALL BUSINESS CONCERN

☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING X : Paulina Ben-Ami

TITLE OF PERSON IF OTHER THAN OWNER X : Vice President

ADDRESS OF PERSON SIGNING X : P.O.Box 95, Rehovot 76100, Israel

SIGNATURE X Paulina Ben-Ami DATE X 29 November 1999

DBP/sfc

SFC PAS213728.1*-10/20/99 11 21 AM

YEDA
RESEARCH AND DEVELOPMENT
CO. LTD.

420 Rec'd PCT/98/14034 72
22 OCT 1999
PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

*This paper or fee is being deposited with the United States Postal Service "Express Mail
Post Office to Addressee" under 37 CFR § 1.10, Mailing Label No. EM341130405US.*

Applicant : Yochay Danziger et al.
Application No. : To Be Assigned
Filed : October 22, 1999
Title : OPTICAL RESONATORS WITH DISCONTINUOUS PHASE
ELEMENTS
Grp./Div. : To Be Determined
Examiner : To Be Determined
Docket No. : 36256/DBP/C608

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Post Office Box 7068
Pasadena, CA 91109-7068
October 22, 1999

Commissioner:

Please amend the above-identified application as follows:

IN THE CLAIMS:

Claim 5, delete "either of the preceding claims 1,2 and 4" and insert therefor -claim 1-.

Claim 6, delete "any of the preceding claims 1, 2, 4 and 5" and insert therefor -claim 1-.

Claim 7, delete "any of the preceding claims 1,2,4, 5 and 6" and insert therefor -claim 1-.

Claim 8, delete "any of the preceding claims 1,2,4, 5 and 6" and insert therefor -claim 1-.

Claim 9, delete "any of the preceding claims" and insert therefor -claim 1-.

Claim 10, delete "any of the preceding claims" and insert therefor -claim 1-.

Claim 11, delete "any of the preceding claims" and insert therefor -claim 1-.

Claim 12, delete "any of the preceding claims" and insert therefor -claim 1-.

Claim 13, delete "any of the preceding claims" and insert therefor -claim 1-.

Claim 14, delete "any of the preceding claims" and insert therefor -claim 1-.

Claim 15, delete "any of the preceding claims" and insert therefor -claim 1-.

Application No. To Be Assigned


REMARKS

In view of the foregoing amendments, consideration and allowance of this application is respectfully requested.

Respectfully submitted,

CHRISTIE, PARKER & HALE, LLP

By



D. Bruce Prout
Reg. No. 20,958
626/795-9900

DBP/sfc

SFC PAS214297.1-*--10/22/99 3:03 PM

420 Rec'd PCT/PTO 22 OCT 1999

OPTICAL RESONATORS WITH DISCONTINUOUS PHASE ELEMENTS

FIELD OF THE INVENTION

The present invention relates to optical resonators generally and to those used in lasers as specific examples of such resonators.

BACKGROUND OF THE INVENTION

In general, the intensity distribution of output light from optical resonators, especially those used in high power lasers with large apertures, is not uniform but has the form of a pattern of either spots or rings, or a combination of these. Such distributions of output light result from the fact that the light inside an optical resonator is distributed in similar patterns termed modes. The spots and rings of this intensity pattern are so distributed that adjacent spots and adjacent rings have opposite phases (π phase shift).

When only the fundamental mode (TEM 00) exists in a resonator, the output light distribution consists of only a single spot, and this mode is considered optimal. However, when higher order modes exist, the light distribution contains multiple spots or rings, so that the focusability and intensity of the output beam decreases. Such a decrease is undesirable for most applications involving laser light.

In order to improve the characteristics of the output light, external phase elements can be introduced into the optical path of the output beam in order to provide controlled phase or amplitude changes to any cross-sectional part of the beam. Examples of such phase elements are presented in the article "How phase plates

transform and control laser beams" by Lee W. Casperson, published in Laser Focus World, May 1994, 223-228. In this article, the phase elements are designed to ensure that all portions of the output laser beam are in phase, thereby improving the far field intensity distribution.

With the introduction of a phase element outside the laser, the usual far field distribution of spots is replaced by a single, intense, on-axis spot surrounded by a pattern of much fainter spots. By this means, the intensity of light distribution resulting from a single high order mode can be increased by a factor of ten or more. Unfortunately, such an increase can only occur when the output light distribution results from a single stable mode.

Several methods have been proposed in order to obtain a specific, stable, high order mode, so the total laser output power is high, and the stability is such that the distribution of the beam can be improved by means of an external phase element. These methods have had limited success. For example, in the article "Single-mode selection using coherent imaging within a slab waveguide CO₂ laser" published in Applied Physical Letters, Vol. 60, 2469-2471 (1992), K. M. Abramski, H. J. Baker, A. D. Colly and D. R. Hall propose the insertion of a wire grid into the laser resonator for selecting a specific high order mode. Unfortunately, the grid and the adjacent resonator mirror are susceptible to damage through heating of the grid by the inter-cavity flux of energy, particularly during mirror alignment.

Another example involves the use of a conical resonator mirror to obtain a single higher order mode. This method was published by M. Rioux, P. A. Belanger and M. Cormier in the article "High-order circular-mode selection in a conical resonator" in Applied Optics, Vol. 16, 1791-1792 (1977). Unfortunately, it is difficult to predict and obtain a specific distribution of the higher order mode output laser beam in order to

design the correct external phase element. In particular, it is difficult to match the orientation of the required external phase element to that of the output light distribution.

In order to obtain a single, stable, lowest order mode TEM 00, an aperture must be inserted into the resonator. When the aperture is small, only the TEM 00 mode with the narrowest field distribution propagates, while higher order modes are eliminated because they are absorbed by the aperture. In general a laser operating with a pure TEM 00 mode has optimal beam quality, but relatively low output power.

In summary it is appreciated that the prior art shows how external phase elements can improve the quality of the output light distribution from an optical resonator, such as a laser. Unfortunately, this improvement cannot be practically implemented with most lasers, especially these operating in multi-mode, so the introduction of external phase elements are indeed limited to very special cases. Furthermore, wires and conical elements used for controlling the modes inside the optical resonator are not practical and tend to reduce the power of the output beam. Intra-cavity apertures, though widely used, reduce the laser power output significantly.

The laser design limitations described above are applicable to both gas and solid state lasers. In addition, there are a number of mode design problems specific to solid state lasers, which limit their performance. Solid state lasers are particularly susceptible to a problem known as thermal lensing of the laser rod, which constitutes the gain material in such lasers. Thermal lensing occurs when the shape or the optical properties of the laser rod change because of the high thermal stresses set up within the rod at high input power levels. The optical elements in a solid state laser are designed to create an optimal mode shape while taking into account thermal lensing of the gain medium at the output power levels at which the laser is designed to operate. However, if the output power of the laser is changed, the thermal lensing of the gain medium changes, and the

optical resonator no longer supports the optimal mode shape. Furthermore, in extreme cases the optical resonator becomes unstable and the output power of the laser drops to zero.

The input power levels to the gain medium over which the optical resonator remains stable define the dynamic range of the laser. It has been shown by Vittorio Magni in the article "Resonators for solid state lasers with large volume fundamental mode and high alignment stability" published in Applied Optics, Vol.25, 107-117 (1986) that the dynamic range of a solid state laser is inversely proportional to the width of the Gaussian mode (0,0) inside the gain medium. The maximum output power is proportional to the width of this mode. Therefore, the dynamic range is inversely proportional to the maximum output power from the laser. This means that when designing a laser, a compromise must be made between the maximum output power of the laser and its dynamic range. This significantly limits the laser's usefulness.

Another problem which limits the performance of solid state lasers arises from the optical distortions set up in the mode structure because of the birefringent nature of the lasing rod. The birefringence introduces areas of circular polarization into the mode because of the different phase shifts introduced along the different crystal axes, and thereby degrades the quality of the laser output beam.

SUMMARY OF THE INVENTION

The present invention seeks to provide an improved optical resonator with an improved output beam.

There is thus provided in accordance with a preferred embodiment of the present invention an optical resonator comprising reflector elements and with at least one discontinuous phase element disposed between the reflector elements. The reflector elements may be full reflectors or output couplers.

The optical resonator may be a passive or active optical resonator. If the optical resonator is an active optical resonator, it may be embodied in a laser, such as an axial laser or a ring laser. The resonator may be a stable or an unstable resonator.

The discontinuous phase element may be embodied in at least one reflector or output coupler or may be positioned adjacent to an optical element or may be placed inside the resonator at a defined point which images onto itself by reflection from one of the above optical components of the resonator.

The discontinuous phase element may provide discontinuous phase change as well as one or more of angular, linear or radial phase change.

The optical resonator may also comprise an external discontinuous phase element operative in addition to the internal element, in order to cancel distortions and eliminate phase discontinuities in the output beam from the optical resonator.

The invention operates by producing sharp changes in the phase distribution of the undesirable modes, so that their propagation losses are sufficiently high to prevent their existence. This is done by introducing a discontinuous phase change to these modes at locations where they have high intensity.

In general the intensity of resonator modes is distributed in well-defined patterns of spots or rings, the phases of neighboring spots or rings having opposite sign (π phase shift). It is possible to predict the field distribution (amplitude and phase) of any mode propagating.

This invention ensures that generally only one desired mode propagates in the optical resonator, with a defined intensity distribution. This is done by incorporating two discontinuous phase elements that introduce different phase changes to different parts (spots and rings) of the mode distribution. In addition, the elements are designed and aligned to ensure that the discontinuous phase change in each element falls at the interfaces between neighboring parts of the selected mode structure, where the intensity is very low. The phase changes introduced by each element must be of opposite sign, so that the sum of the combined phase change is either zero or a multiple of 2π .

If the distance between the two discontinuous phase elements inside the resonator is sufficiently short, then the total intensity distribution of the desired mode does not change as it passes through the two elements because the phase change introduced by one element is canceled by the other. The other, undesired modes have a different distribution of intensity, so that when they pass through the first discontinuous phase element, they suffer a sharp phase change at locations where their intensity is strong. This results in a strong divergence, so that the second discontinuous phase element can no longer cancel the phase changes introduced by the first element. These modes therefore suffer a loss of intensity and are suppressed.

Similar results can be achieved by using only a single discontinuous phase element. With the single element, the phase change introduced by the element must be either zero or π , and the element should be located near one of the resonator mirrors, preferably near the output coupler mirror. After the desired mode passes once through the element, all parts of its intensity distribution are in phase (zero or 2π phase difference). The mirror then reflects the modified mode so it passes once more through the element, and all parts of the intensity distribution return to their original phase. This

is due to the fact that the total phase change introduced by the element is 2π , which is equivalent to no change at all.

It is possible for the second passage of the mode through the discontinuous phase element to take place at a point in the resonator far from that of the first passage, on condition that the two passages are made at planes which are conjugate image planes produced by some optical component in the resonator.

An additional phase element may be placed outside the resonator in order to further improve the output beam. This element can easily be characterized since the resonator output beam originates from a single well defined stable mode.

A suitably constructed discontinuous phase element may be inserted at the correct position into the cavity of a solid state laser designed with a conventional optical resonator to support a narrow Gaussian mode. The addition of the discontinuous phase element forces the resonator to oscillate in a high order mode, resulting in a laser which combines high maximum output power without the limitations of dynamic range of the conventional cavity.

Likewise, a suitably constructed discontinuous phase element inserted into the cavity of a solid state laser at the correct position, can also compensate for birefringence distortions introduced by the gain medium.

Likewise, a suitably constructed discontinuous phase element can be inserted into the cavity of a laser that has a flat output coupler and a curved full reflector. The placement of the discontinuous phase element adjacent to the flat output coupler leads to lower divergence of the output beam.

Likewise, a suitably constructed discontinuous phase element inserted into the cavity of an unstable resonator laser at the correct position. will force the resonator to

oscillate in a high order mode, and will thereby prevent the high intensity center spot produced in unstable resonators operating in the lowest order mode.

Thus, in accordance with the above embodiments, single mode operation and high beam quality can be achieved even in a resonator with a large aperture, and hence, high output power. The design of the discontinuous phase element can vary from one resonator to the other but there are several inherent features common to all such elements. The phases of these elements all have lines of discontinuity, and these lines are positioned where the intensity of the desired mode is expected to be very low. In addition, the discontinuous phase changes are introduced to the mode inside the resonator at planes which are located at defined distances from each other.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be understood and appreciated more fully from the following detailed description taken in conjunction with the drawings, in which:

Figs. 1A and 1B are schematic illustrations of axial lasers constructed and operative in accordance with a preferred embodiment of the present invention; Fig. 1A shows such a laser with a curved output coupler, while Fig. 1B shows a similar laser with a flat output coupler.

Fig 2 is a schematic illustration of an output coupler arrangement useful in the laser of Fig. 1A, and including a combination of a conventional output coupler and a discontinuous phase element:

Fig. 3 is a schematic illustration of an output coupler arrangement useful in the laser of Fig. 1A and including a hybrid element which consists of an output coupler and a discontinuous phase element:

Fig. 4 is a schematic illustration of a discontinuous phase element designed to select mode (6,1) in a rectangle resonator;

Fig. 5 is a schematic illustration of a discontinuous phase element designed to select mode (2,0) in a cylindrical resonator;

Fig. 6 is a schematic illustration of a discontinuous phase element combined with a spiral phase element. This element is designed to select mode (1,1)* in a cylindrical resonator;

Fig. 7 presents a schematic illustration of a discontinuous phase element 212 designed to select mode (0,4) in a cylindrical resonator;

Figs. 8A, 8B, 8C and 8D are cross-sections of the intensity distribution of the first four modes having the lowest intensity loss, inside a rectangular conventional resonator;

Fig. 9 is an illustration of the amplitude distribution of mode (2,0) in a rectangular resonator;

Fig. 10 is an illustration of the amplitude distribution of mode (2,0) which was presented in Fig. 8C, after passing through the discontinuous phase element;

Fig. 11 is an illustration of the amplitude distribution of mode (1,0) in a rectangular resonator;

Fig. 12 is an illustration of the amplitude distribution of mode (1,0) which was presented in Fig. 11, after passing through the discontinuous phase element designed to select mode (2,0);

Figs. 13A, 13B, 13C and 13D are cross-sections of the intensity distributions of the first four modes having the lowest intensity loss, inside a rectangular resonator with a discontinuous phase element designed to select mode (2,0);

Fig. 14 presents the intensity loss of the four lowest order modes in a rectangular resonator designed to select mode $(2,0)$, as a function of the axial displacement of the discontinuous phase element from the output coupler;

Fig. 15 is a description of the far field of the output beam from a resonator with a discontinuous phase element designed to select mode $(2,0)$. The beam converges to a single lobe with high intensity and good quality;

Fig. 16 is an illustration of an axial laser with one discontinuous optical element placed close to a plane which is imaged onto itself after reflection from the back mirror. This situation is optically equivalent to placing the element close to the output coupler;

Fig. 17 is an illustration of a ring laser with two discontinuous optical elements placed close to each other. A third element is placed outside the resonator in order to improve the output beam;

Fig. 18 is a representation of the linear polarization of the $(0,0)$ mode in a cylindrical Nd:YAG crystal of a solid state laser;

Fig. 19 is a schematic illustration of the polarization distortion introduced into the $(0,0)$ mode because of the birefringence of the crystal of Fig. 18;

Fig. 20 is a view of the polarization structure of the $(0,2)$ cylindrical mode in the Nd:YAG crystal of a solid state laser, showing the π phase shift between adjacent parts of the mode structure; and

Fig. 21 is a schematic illustration of a single discontinuous phase element designed to select mode $(0,2)$ and to compensate for birefringence in the Nd:YAG crystal of a solid state laser

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Reference is now made to Fig. 1 which is a schematic illustration of an axial laser, as an example of an optical resonator, constructed and operative in accordance with a preferred embodiment of the present invention. The axial laser comprises reflectors, preferably a full reflector 20 and a partial reflector or an output coupler 22, disposed at opposite ends of an optical resonator 24, which contains a gain medium 26, and with a discontinuous phase element 86 located between the full reflector 20 and the output coupler 22.

A mode, indicated by reference number 30, is seen to propagate back and forth between the reflector 20 and the output coupler 22, while passing through the gain medium 26. A beam of light 32 is emitted through the output coupler 22. The width of mode 30 inside the laser is influenced by an aperture 34.

In accordance with a preferred embodiment of the invention, the laser of Fig. 1A is characterized in that it includes at least one discontinuous phase element operative to introduce discontinuous phase changes to the modes propagating inside the resonator, so that the divergence of the undesirable modes is greater than that of the desired mode. This results in a broadening of the undesirable mode intensity distribution, preventing their propagation in the laser. Thus the undesirable modes are suppressed, thereby improving the quality of the output beam.

Preferably, one discontinuous phase element is employed. This element should be placed close to the output coupler but not too close. Alternatively, the element can be placed near a plane that can be imaged onto itself by the optics of the laser. When two elements are used, they should be placed close to each other or close to two planes that can be imaged onto each other by the optics inside the laser.

There are a number of alternative optical configurations of such axial lasers, wherein the output coupler and full reflector can have different curvatures, concave or convex, or even be flat. Fig. 1B shows one such configuration, commonly used in industrial lasers, in which the output coupler 23 is flat, and the full reflector 20 is concave, like that of the laser shown in Fig. 1A. Discontinuous phase elements can be used to improve the output beams of all these types of lasers. For example, a discontinuous phase element 86 inserted into the cavity configuration shown in Fig. 1B, next to the flat output coupler 23, results in low divergence of the output beam 32, while the curved full reflector may compensate for lensing effects of the gain medium.

Two alternative embodiments of an output coupler arrangement including a discontinuous phase element are now described with reference to Figs. 2 and 3.

Fig. 2 is a schematic illustration of an output coupler arrangement useful in the laser of Fig. 1A and including a combination of a conventional output coupler 80, with a discontinuous phase element 86.

The conventional output coupler is preferably coated with a partial reflecting coating on surface 82 and an antireflection coating on surface 84. The discontinuous phase element is coated with an antireflection coating on both surfaces 88 and 90.

The discontinuous phase element is constructed to be compatible with the desired mode intensity distribution. Specifically, it is desired to form phase discontinuities at locations where the desired mode has little or no intensity. The magnitude of each phase discontinuity is π , so that after the desired mode passes once through the discontinuous phase element, all parts of the cross-sectional intensity distribution of the desired mode have the same phase. After the second pass through the element the desired mode returns to its original distribution.

The embodiment of Fig. 3 combines elements 80 and 86 of the embodiment of Fig. 2 to achieve a single hybrid element 100 having less surfaces. The surface 102 of the hybrid element may have the same form as surface 90 in the embodiment of Fig. 2, while the partially reflective surface 104 may have the same form as surface 82 in embodiment of Fig. 2.

Figs. 4, 5 and 6 present examples of discontinuous phase elements constructed to select various types of modes. These elements may be realized by photolithographic methods, by mechanical methods such as diamond turning, by mechanical methods such as graded index elements or any other method which produces an element that changes the phase of a wave-front.

Fig. 4 presents a schematic illustration of a discontinuous phase element constructed to select mode (6,1) in a rectangle resonator. In mode (6,1) there are 14 sections in which the energy is concentrated. The element is designed to have constant phases at each location 90. The discontinuous lines 95 are located at the boundaries of these sections.

Fig. 5 presents a schematic illustration of a discontinuous phase element 204 constructed to select mode (2,0) in a cylindrical resonator. The mode notation (r,θ) indicates the number of radial, r , and angular, θ , nodes in a cylindrical mode pattern. The intensity distribution in the (2,0) mode is distributed in rings, where adjacent rings provide a π phase shift, and the discontinuities 200 are circles.

Fig. 6 presents a schematic illustration of a discontinuous phase element 208 combined with a spiral phase element. The element is constructed to select mode (1,1)* in a cylindrical resonator. This cylindrical mode is unlike that previously described in Fig. 5, in that it has angular as well as radial phase distribution. It appears as two concentric rings. The circular discontinuities 210 select the desired radial distribution,

and discriminate between other $(n,1)^*$ modes, which have a different number of rings, according to the value of n . The spiral element selects the desired angular phase distribution of the mode and ensures that modes with a different angular distribution suffer rapid broadening and decay after very few traverses of the element.

Fig. 7 presents a schematic illustration of a discontinuous phase element 212 constructed to select mode $(0,4)$ in a cylindrical resonator. Such an element is insensitive to radial perturbations of the amplitude distribution of the mode, such as would accrue from the effects of thermal lensing in a solid state laser.

The mechanism for mode discrimination and consequent output beam quality improvement according to the present invention will now be described with the aid of Figs. 8A-D, 9, 10, 11, 12, 13A-D, 14 and 15.

Figs. 8A, 8B, 8C and 8D present the intensity distributions of the first four modes having the lowest intensity loss, inside a rectangle conventional resonator. The intensity is distributed in a well defined sections 220 with significant intensities, separated by sections 222 with little, if any, intensity

Fig. 9 shows the amplitude distribution of mode $(2,0)$ in a rectangle resonator. The corresponding intensity distribution of this mode was presented in Fig. 8C. The amplitude of this mode is positive in the central section 240 and negative in the two side sections 244.

Fig. 10 shows the amplitude distribution of the mode $(2,0)$ presented in Fig. 9, after passing once through the discontinuous phase element designed to select this mode. The sign of the amplitude in the central section 250 as well as in the side sections 254 are now all positive. This shape of the mode converges slowly as the mode propagates, and a converging output beam exits the output coupler located next to the discontinuous phase element. Some of the mode is reflected from the output coupler, as

illustrated in Figs. 2 and 3, and passes again through the discontinuous phase element. The optical path between the first passage and the second passage through the phase element is very short, so that after the second passage through the phase element, the amplitude distribution of the mode returns to its original distribution shown in Fig.9.

Other modes with a differing amplitude distribution are affected differently by the passage through the discontinuous phase element, so they rapidly decay and cease to exist as will be illustrated with the example shown in Figs. 11 and 12.

Fig. 11 presents the amplitude distribution of mode (1,0) .

Fig. 12 presents the amplitude distribution of mode (1,0) shown in Fig. 11, after passing once through the discontinuous phase element designed to select mode (2,0) . Two sharp discontinuous phase shifts 261 are introduced at locations where the amplitude of mode (1,0) is significant. These discontinuities ensure that mode (1,0) diverges rapidly so that it does not return to its original shape after the second passage through the phase element. As a result, a large intensity loss for mode (1,0) accrues and this mode ceases to exist.

Figs. 13A, 13B, 13C and 13D present the intensity distributions of the first four modes having the lowest intensity losses, inside a rectangle resonator with a discontinuous phase element designed to select mode (2,0). Only the intensity distribution of the desired mode (2,0), presented in Fig. 13A remains the same. The distributions of the other modes are distorted, and, being strongly attenuated, die out after a small number of resonator traverses.

Fig. 14 presents the losses for the four lowest order modes as a function of distance of the discontinuous phase element from the output coupler, for a rectangular axial resonator. The discontinuous phase element is designed to select mode (2,0). If the discontinuous phase element is placed very close or against the output coupler 280,

even the undesired modes are not distorted by the phase element, since there is no axial space for them to diverge before being reflected back for a second passage through the discontinuous phase element, where they are converted back to their original amplitude distribution. When the distance between the discontinuous phase element and the output coupler increases, then the undesired modes immediately start to diverge, resulting in sharply increased losses 282, while the desired mode have little loss 283. At a slightly increased distance, only the desired mode exist inside the laser. When the distance between the discontinuous phase element and the output coupler increases further, even the desired mode has a significant loss of intensity 284.

Fig. 15 presents the far field intensity distribution of the output beam resulting from mode (2,0). As is evident, the beam converges to a single lobe with high intensity and good quality 285.

Reference is now made to Fig. 16, which schematically presents a configuration of an axial laser with a single discontinuous phase element 302 placed at an arbitrary point inside the resonator and not close to the output coupler 304 or the reflector 306. In this embodiment the phase element is placed close to a point that is being imaged to itself by the output coupler 304 and/or the reflector 306, or by any other optical elements inside the resonator. This imaging configuration resembles the configuration with two phase elements placed close to each other.

In this embodiment the intensity distribution of the selected mode is different in each of two axial sections of the overall laser. In the first section 308, on the output coupler side of the discontinuous phase element, the mode is converging and its cross-sectional intensity is high because the phases of all parts of the intensity pattern are the same. In the second section 310, on the reflector side of the discontinuous phase element, the shape of the mode is broad with low intensity because the phases of some

parts of the intensity pattern are not the same. This embodiment is applicable, for example, in lasers which use the nonlinear properties of crystals for changing the radiation wavelength and/or for mode locking. The broader section 310, with its high filling factor, is useful for efficiently obtaining increased gain from the gain medium 312, while the narrow section 308, with its high field intensity, is useful for wavelength conversion by the nonlinear crystal 314.

Reference is now made to Fig. 17, which schematically presents a ring resonator having two discontinuous phase elements. The optical properties of these elements are the same as described earlier. The discontinuous phase elements 350 are designed to have opposite phases, so together do not influence the distribution of the desired mode. Other modes are distorted, however, as previously described in the axial laser case. In this configuration the phase discontinuities introduced by the elements may be arbitrary and need not be exactly π . The intensity distribution of the output beam is the same as that of the mode inside the laser. Thus, in order to improve the distribution of the output beam a third external phase element must be introduced at the output from the laser.

Alternative configurations for this ring embodiment are similar to those presented for the axial resonator. The two phase elements can be combined into a single element with phase patterns on both sides. They can be placed far apart, provided that they are imaged onto each other by some optical element in the resonator. A single phase element can be used instead of two, provided that after one round-trip, the emerging wave-front from the element is imaged onto itself.

Figs. 18, 19, 20 and 21 describe how a discontinuous phase element compensates for the problem of birefringence distortion in the gain medium of a solid state laser.

Fig. 18 is a schematic illustration of mode (0,0) marked as 401. The arrow in the illustration represents the linear polarization of this mode. After this mode passes once

through the distorting medium, for example a cylindrical Nd:YAG crystal, its polarization is distorted.

Fig. 19 is a schematic illustration of the polarization distortions introduced to the mode by the crystal due to birefringence. The primary axes of the polarization are marked as 403 and 405. Along these axes, the polarization remains linear, but different phase shifts are introduced to the mode along them. In between these axes, the polarization of the mode becomes circular (407). The circular polarization and the phase shifts introduced to the different sections of the mode, distort the mode and consequently reduce the quality of the output beam of the laser.

Fig. 20 describes, schematically, mode (0,2) in cylindrical coordinates. The arrows represent a linear polarization where sections 412 and sections 414 of the mode have π phase shift between them, as previously described. After this mode passes through the distorting gain medium, small areas with circular polarization arise, although most of the energy of the mode is concentrated along the primary axes. However, the phase difference between the various sections 412 and 414 is no longer π . This phase distortion can be easily compensated by the use of a suitable discontinuous phase element.

Fig. 21 is a schematic illustration of a single discontinuous phase element designed to select mode (0,2) and to compensate for birefringence in the gain medium described in Fig.19. The phase difference between the various sections of the element (417 and 419) is $\pi - \Delta$, where Δ is the phase difference introduced into the two sections of the mode (412 and 414) by the birefringence distortion of the gain medium.

It will be appreciated by persons skilled in the art that the present invention is not limited by what has been particularly shown and described hereinabove. Rather the scope of the present invention includes both combinations and subcombinations of

various features described hereinabove as well as variations and modifications thereto which would occur to a person of skill in the art upon reading the above description and which are not in the prior art.

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661

CLAIMS

We claim:

1. An optical resonator comprising reflector elements and at least one discontinuous phase element disposed between said reflector elements.
2. An optical resonator according to claim 1, and whose said reflector elements are at least one full reflector and an output coupler.
3. An optical resonator according to either of the preceding claims, and being a passive optical resonator.
4. An optical resonator according to either of the preceding claims 1 and 2, and being an active optical resonator.
5. An optical resonator according to either of the preceding claims 1, 2 and 4, and being the resonator of a laser.
6. An optical resonator according to any of the preceding claims 1, 2, 4 and 5, and being the resonator of a ring laser.
7. An optical resonator according to any of the preceding claims 1, 2, 4, 5 and 6, being a stable resonator.
8. An optical resonator according to any of the preceding claims 1, 2, 4, 5 and 6, and being an unstable resonator.
9. An optical resonator according to any of the preceding claims, and wherein said at least one discontinuous phase element is embodied in a reflector of said optical resonator.
10. An optical resonator according to any of the preceding claims, and wherein said at least one discontinuous phase element is embodied in an output coupler of said optical resonator.

11. An optical resonator according to any of the preceding claims, and wherein said at least one discontinuous phase element is positioned adjacent to an optical element of said optical resonator.

12. An optical resonator according to any of the preceding claims, and wherein said at least one discontinuous phase element is placed inside said optical resonator at a defined point which is imaged onto itself from an optical element within the resonator.

13. An optical resonator according to any of the preceding claims, and wherein said at least one discontinuous phase element is positioned adjacent to a flat output coupler of said optical resonator, and the full reflector of said resonator may be curved.

14. An optical resonator according to any of the preceding claims, and wherein said at least one discontinuous phase element provides discontinuous phase change as well as at least one of angular, linear and radial phase change.

15. An optical resonator according to any of the preceding claims, and also comprising an external discontinuous phase element operative in addition to the internal element in order to cancel distortions and eliminate phase discontinuities in an output beam from said optical resonator.

1/10

FIG. 1A




FIG. 1B




FIG. 2





FIG. 3



2/10

FIG. 4





FIG. 5



3/10

FIG. 6





FIG. 7



4/10

FIG. 8A




FIG. 8B




FIG. 8C





FIG. 8D



5/10

FIG. 9





FIG. 10



6/10

FIG. 11









FIG. 12



7/10



8/10

FIG. 14





FIG. 15



9/10




FIG. 16

FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 1A




FIG. 1B




FIG. 2





FIG. 3



2/10

FIG. 4





FIG. 5



3/10

FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C





FIG. 8D



5/10

09/403472

FIG. 9





FIG. 10



6/10

FIG. 11





FIG. 12



Relative
intensity




FIG. 13A

Spatial Distance

Relative
intensity




FIG. 13B

Spatial Distance

Relative
intensity




FIG. 13C

Spatial Distance

Relative
intensity




FIG. 13D

Spatial Distance

09/403472

8/10

FIG. 14





FIG. 15






FIG. 16

FIG. 17




FIG. 18




FIG. 19




FIG. 20





FIG. 21



DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATIONS

PATENT

Docket No. : 36256/DBP/C608

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **OPTICAL RESONATORS WITH DISCONTINUOUS PHASE ELEMENTS**, the specification of which is attached hereto unless the following is checked:

X was filed on 29.April.1998 as United States Application Number or PCT International Application Number PCT/IL98/00204 and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of the foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

<u>Application Number</u>	<u>Country</u>	<u>Filing Date (day/month/year)</u>	<u>Priority Claimed</u>
120754	Israel	01.May.1997	Yes

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below.

Application Number Filing Date

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

Application Number Filing Date Patented/Pending/Abandoned

POWER OF ATTORNEY: I hereby appoint the following attorneys and agents of the law firm CHRISTIE, PARKER & HALE, LLP to prosecute this application and any international application under the Patent Cooperation Treaty based on it and to transact all business in the U.S. Patent and Trademark Office connected with either of them in accordance with instructions from the assignee of the entire interest in this application; or from the first or sole inventor named below in the event the application is not assigned; or from SANFORD

**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATIONS**

Docket No. 36256/DBP/C608

T. COLB & CO. in the event the power granted herein is for an application filed on behalf of a foreign attorney or agent.

R. W. Johnston	(17,968)	John D. Carpenter	(34,133)	Lucinda G. Auciello	(42,270)
D. Bruce Prout	(20,958)	David A. Plumley	(37,208)	Norman E. Carte	(30,455)
Hayden A. Carney	(22,653)	Wesley W. Monroe	(39,778)	Joel A. Kauth	(41,886)
Richard J. Ward, Jr.	(24,187)	John W. Eldredge	(37,613)	Patrick Y. Ikehara	(42,681)
Russell R. Palmer, Jr.	(22,994)	Gregory S. Lampert	(35,581)	Mark Garscia	(31,953)
LeRoy T. Rahn	(20,356)	Grant T. Langton	(39,739)	Gary J. Nelson	(44,257)
Richard D. Seibel	(22,134)	Constantine Marantidis	(39,759)	Raymond R. Tabandeh	(43,945)
Walter G. Maxwell	(25,355)	Daniel R. Kimbell	(34,849)	Phuong-Quan Hoang	(41,839)
William P. Christie	(29,371)	Craig A. Gelfound	(41,032)	Jun-Young E. Jeon	(43,693)
David A. Dillard	(30,831)	Syed A. Hasan	(41,057)	Kathy Mojibi	(41,409)
Thomas J. Daly	(32,213)	Kathleen M. Olster	(42,052)	Cynthia A. Bonner	(44,548)
Vincent G. Gioia	(19,959)	Daniel M. Cavanagh	(41,661)	Marc A. Karish	(44,816)
Edward R. Schwartz	(31,135)	Molly A. Holman	(40,022)		

The authority under this Power of Attorney of each person named above shall automatically terminate and be revoked upon such person ceasing to be a member or associate of or of counsel to that law firm.

DIRECT TELEPHONE CALLS TO : D. Bruce Prout, 626/795-9900

**SEND CORRESPONDENCE TO : CHRISTIE, PARKER & HALE, LLP
P.O. Box 7068, Pasadena, CA 91109-7068**

I declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first joint inventor Yochay Danziger	Inventor's signature	Date
Residence and Post Office Address Sdeh Nachum Street 5/26, 75284 Rishon LeZion, Israel		Citizenship Israeli

Full name of second joint inventor Asher A. Friesem	Inventor's signature	Date
Residence and Post Office Address Weizmann Institute of Science, Neve Metz 15, 76100 Rehovot, Israel		Citizenship Israeli

Full name of third joint inventor Ram Oron	Inventor's signature	Date
Residence and Post Office Address Busel Street 26, 76404 Rehovot, Israel		Citizenship Israeli

**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATIONS**

PATENT

Docket No. : 36256/DBP/C608

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **OPTICAL RESONATORS WITH DISCONTINUOUS PHASE ELEMENTS**, the specification of which is attached hereto unless the following is checked:

X was filed on 29.April.1998 as United States Application Number or PCT International Application Number PCT/IL98/00204 and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of the foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

<u>Application Number</u>	<u>Country</u>	<u>Filing Date (day/month/year)</u>	<u>Priority Claimed</u>
120754	Israel	01.May.1997	Yes

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below.

<u>Application Number</u>	<u>Filing Date</u>
---------------------------	--------------------

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

<u>Application Number</u>	<u>Filing Date</u>	<u>Patented/Pending/Abandoned</u>
---------------------------	--------------------	-----------------------------------

POWER OF ATTORNEY: I hereby appoint the following attorneys and agents of the law firm CHRISTIE, PARKER & HALE, LLP to prosecute this application and any international application under the Patent Cooperation Treaty based on it and to transact all business in the U.S. Patent and Trademark Office connected with either of them in accordance with instructions from the assignee of the entire interest in this application; or from the first or sole inventor named below in the event the application is not assigned; or from SANFORD

**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATIONS**

Docket No. 36256/DBP/C608

38

T. COLB & CO. in the event the power granted herein is for an application filed on behalf of a foreign attorney or agent.

R. W. Johnston	(17,968)	John D. Carpenter	(34,133)	Lucinda G. Auciello	(42,270)
D. Bruce Prout	(20,958)	David A. Plumley	(37,208)	Norman E. Carte	(30,455)
Hayden A. Carney	(22,653)	Wesley W. Monroe	(39,778)	Joel A. Kauth	(41,886)
Richard J. Ward, Jr.	(24,187)	John W. Eldredge	(37,613)	Patrick Y. Ikehara	(42,681)
Russell R. Palmer, Jr.	(22,994)	Gregory S. Lampert	(35,581)	Mark Garscia	(31,953)
LeRoy T. Rahn	(20,356)	Grant T. Langton	(39,739)	Gary J. Nelson	(44,257)
Richard D. Seibel	(22,134)	Constantine Marantidis	(39,759)	Raymond R. Tabandeh	(43,945)
Walter G. Maxwell	(25,355)	Daniel R. Kimbell	(34,849)	Phuong-Quan Hoang	(41,839)
William P. Christie	(29,371)	Craig A. Gelfound	(41,032)	Jun-Young E. Jeon	(43,693)
David A. Dillard	(30,831)	Syed A. Hasan	(41,057)	Kathy Mojibi	(41,409)
Thomas J. Daly	(32,213)	Kathleen M. Olster	(42,052)	Cynthia A. Bonner	(44,548)
Vincent G. Gioia	(19,959)	Daniel M. Cavanagh	(41,661)	Marc A. Karish	(44,816)
Edward R. Schwartz	(31,135)	Molly A. Holman	(40,022)		

The authority under this Power of Attorney of each person named above shall automatically terminate and be revoked upon such person ceasing to be a member or associate of or of counsel to that law firm.

DIRECT TELEPHONE CALLS TO : D. Bruce Prout, 626/795-9900
SEND CORRESPONDENCE TO : CHRISTIE, PARKER & HALE, LLP
P.O. Box 7068, Pasadena, CA 91109-7068

I declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first joint inventor Yochay Danziger	Inventor's signature <i>[Signature]</i>	Date 28/12/00
Residence and Post Office Address Sdeh Nachum Street 5/26, 75284 Rishon LeZion, Israel		Citizenship Israeli


Full name of second joint inventor Asher A. Friesem	Inventor's signature <i>[Signature]</i>	Date
Residence and Post Office Address Weizmann Institute of Science, Neve Metz 15, 76100 Rehovot, Israel		Citizenship Israeli

Full name of third joint inventor Ram Oron	Inventor's signature <i>[Signature]</i>	Date
Residence and Post Office Address Busel Street 26, 76404 Rehovot, Israel		Citizenship Israeli

**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATIONS**

PATENT

Docket No. : 36256/DBP/C608



As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **OPTICAL RESONATORS WITH DISCONTINUOUS PHASE ELEMENTS**, the specification of which is attached hereto unless the following is checked:

☒ was filed on 29 April 1998 as United States Application Number or PCT International Application Number PCT/IL98/00204 and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of the foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

<u>Application Number</u>	<u>Country</u>	<u>Filing Date (day/month/year)</u>	<u>Priority Claimed</u>
120754	Israel	01 May 1997	Yes

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below.

<u>Application Number</u>	<u>Filing Date</u>
---------------------------	--------------------

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

<u>Application Number</u>	<u>Filing Date</u>	<u>Patented/Pending/Abandoned</u>
---------------------------	--------------------	-----------------------------------

POWER OF ATTORNEY: I hereby appoint the following attorneys and agents of the law firm CHRISTIE, PARKER & HALE, LLP to prosecute this application and any international application under the Patent Cooperation Treaty based on it and to transact all business in the U.S. Patent and Trademark Office connected with either of them in accordance with instructions from the assignee of the entire interest in this application; or from the first or sole inventor named below in the event the application is not assigned; or from SANFORD



**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATIONS**

Docket No. 36256/DBP/C608

38

T. COLB & CO. in the event the power granted herein is for an application filed on behalf of a foreign attorney or agent.

R. W. Johnston	(17,968)	John D. Carpenter	(34,133)	Lucinda G. Auciello	(42,270)
D. Bruce Prout	(20,958)	David A. Plumley	(37,208)	Norman E. Carte	(30,455)
Hayden A. Carney	(22,653)	Wesley W. Monroe	(39,778)	Joel A. Kauth	(41,886)
Richard J. Ward, Jr.	(24,187)	John W. Eldredge	(37,613)	Patrick Y. Ikehara	(42,681)
Russell R. Palmer, Jr.	(22,994)	Gregory S. Lampert	(35,581)	Mark Garscia	(31,953)
LeRoy T. Rahn	(20,356)	Grant T. Langton	(39,739)	Gary J. Nelson	(44,257)
Richard D. Seibel	(22,134)	Constantine Marantidis	(39,759)	Raymond R. Tabandeh	(43,945)
Walter G. Maxwell	(25,355)	Daniel R. Kimbell	(34,849)	Phuong-Quan Hoang	(41,839)
William P. Christie	(29,371)	Craig A. Gelfound	(41,032)	Jun-Young E. Jeon	(43,693)
David A. Dillard	(30,831)	Syed A. Hasan	(41,057)	Kathy Mojibi	(41,409)
Thomas J. Daly	(32,213)	Kathleen M. Olster	(42,052)	Cynthia A. Bonner	(44,548)
Vincent G. Gioia	(19,959)	Daniel M. Cavanagh	(41,661)	Marc A. Karish	(44,816)
Edward R. Schwartz	(31,135)	Molly A. Holman	(40,022)		

The authority under this Power of Attorney of each person named above shall automatically terminate and be revoked upon such person ceasing to be a member or associate of or of counsel to that law firm.

DIRECT TELEPHONE CALLS TO : D. Bruce Prout, 626/795-9900
SEND CORRESPONDENCE TO : CHRISTIE, PARKER & HALE, LLP
 P.O. Box 7068, Pasadena, CA 91109-7068

I declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first joint inventor Yochay Danziger	Inventor's signature X	Date X
Residence and Post Office Address Sdeh Nachum Street 5/26, 75284 Rishon LeZion, Israel		Citizenship Israeli

Full name of second joint inventor Asher A. Eriesem	Inventor's signature A. A. Eriesem	Date Nov. 17/99
Residence and Post Office Address Weizmann Institute of Science, Neve Metz 15, 76100 Rehovot, Israel		Citizenship Israeli

Full name of third joint inventor Ram Oron	Inventor's signature R. Oron	Date Nov 17, 1999
Residence and Post Office Address Busel Street 26, 76404 Rehovot, Israel		Citizenship Israeli

**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATIONS**

Docket No. 36256/DBP/C608

T. COLB & CO. in the event the power granted herein is for an application filed on behalf of a foreign attorney or agent.

R. W. Johnston	(17,968)	John D. Carpenter	(34,133)	Lucinda G. Auciello	(42,270)
D. Bruce Prout	(20,958)	David A. Plumley	(37,208)	Norman E. Carte	(30,455)
Hayden A. Carney	(22,653)	Wesley W. Monroe	(39,778)	Joel A. Kauth	(41,886)
Richard J. Ward, Jr.	(24,187)	John W. Eldredge	(37,613)	Patrick Y. Ikehara	(42,681)
Russell R. Palmer, Jr.	(22,994)	Gregory S. Lampert	(35,581)	Mark Garscia	(31,953)
LeRoy T. Rahn	(20,356)	Grant T. Langton	(39,739)	Gary J. Nelson	(44,257)
Richard D. Seibel	(22,134)	Constantine Marantidis	(39,759)	Raymond R. Tabandeh	(43,945)
Walter G. Maxwell	(25,355)	Daniel R. Kimbell	(34,849)	Phuong-Quan Hoang	(41,839)
William P. Christie	(29,371)	Craig A. Gelfound	(41,032)	Jun-Young E. Jeon	(43,693)
David A. Dillard	(30,831)	Syed A. Hasan	(41,057)	Kathy Mojibi	(41,409)
Thomas J. Daly	(32,213)	Kathleen M. Olster	(42,052)	Cynthia A. Bonner	(44,548)
Vincent G. Gioia	(19,959)	Daniel M. Cavanagh	(41,661)	Marc A. Karish	(44,816)
Edward R. Schwartz	(31,135)	Molly A. Holman	(40,022)		

The authority under this Power of Attorney of each person named above shall automatically terminate and be revoked upon such person ceasing to be a member or associate of or of counsel to that law firm.

DIRECT TELEPHONE CALLS TO : D. Bruce Prout, 626/795-9900

**SEND CORRESPONDENCE TO : CHRISTIE, PARKER & HALE, LLP
P.O. Box 7068, Pasadena, CA 91109-7068**

I declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

On behalf of Yochay Danziger

Full name of sole or first joint inventor Yochay Danziger	Inventor's signature <i>[Signature]</i>	Date Jan 12, 2000
Residence and Post Office Address Sdeh Nachum Street 5/26, 75284 Rishon LeZion, Israel		Citizenship Israeli

Full name of second joint inventor Asher A. Friesem	Inventor's signature <i>[Signature]</i>	Date Nov. 17/99
Residence and Post Office Address Weizmann Institute of Science, Neve Metz 15, 76100 Rehovot, Israel		Citizenship Israeli

Full name of third joint inventor Ram Oron	Inventor's signature <i>[Signature]</i>	Date Nov 17, 1999
Residence and Post Office Address Busel Street 26, 76404 Rehovot, Israel		Citizenship Israeli